

Electrical Feed Rod Rose Ø 140 mm

Designed by Vincent Van Duysen, 2017



Length: 11.81 - Ceiling surface

Adjustable 25 mm, to adapt it to irregular ceilings.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light sources included	no
Number of lamps	1

Physical

Color	White
Trim	No
Length (in)	11.81
IP internal	20



Download

- Family spec sheet [ZIP](#)
- Mounting instructions [PDF](#)



Electrical

Emergency type No

Notes

The closure terminals will also be electrified and must be ordered separately. Rod with a Ø140 connection rose: a supply rod for remote installation of the power supply through the connection rose. Adjustable 25 mm, to adapt it to irregular ceilings.

Accessories & Power Supply



REQUIRED
Power supply
LEDSB96W48V-NDM-D01
LED Driver, 48VDC, 96W, Non-Dimming, 120-277V



REQUIRED
Power supply
LEDSB60W48V-NDM-D01
LED Driver, 48VDC, 60W, Non-Dimming, 120-277V



REQUIRED
Power supply
ACCESSORYTYPE1
LEDSB30W48V-NDM-D01
LED power supply source for remote installation, 48V/30W



REQUIRED
Component
06.5135.14A
End Cap Dali/1-10V/FLOS Control® by Casambi compatible



REQUIRED
Component
06.5135.40A
End Cap Dali/1-10V/FLOS Control® by Casambi compatible



REQUIRED
Component
06.5142.14A
End Cap On board dimmer/FLOS Control® by Casambi compatible



REQUIRED
Component
06.5142.40A
End Cap On board dimmer/FLOS Control® by Casambi compatible