

Electrical Feed Rod Rose Ø 50 mm

Designed by Vincent Van Duysen, 2017



Length: 100 - Ceiling surface

Adjustable 25 mm, to adapt it to irregular ceilings.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light sources included	no
Number of lamps	1

Physical

Colour	Black
Trim	No
Length (mm)	100
Net weight (kg)	0.45
IP internal	20
IP external	20



Download

Mounting instructions



Electrical

Emergency No

Notes

The closure terminals will also be electrified and must be ordered separately. Rod with a Ø50 connection rose: a supply rod for remote installation of the power supply in an accessible place. Adjustable 25 mm, to adapt it to irregular ceilings.

Accessories & Power Supply



REQUIRED
Power supply
ACCESSORYTYPE1

60.8919
LED Power Supply Source for
remote installation. 48V/320W.
100/240 Vac



REQUIRED
Power supply
ACCESSORYTYPE1

60.9170
LED power supply source for
remote installation, 48V/120W.
220/240 Vac



REQUIRED
Power supply
ACCESSORYTYPE1

60.9607
LED power supply source for
remote installation, 110Vac-150W
/ 220Vac-200W



REQUIRED
Component
06.5135.14A
End Cap Dali/1-10V/FLOS
Control® by Casambi compatible



REQUIRED
Component
06.5135.40A
End Cap Dali/1-10V/FLOS
Control® by Casambi compatible



REQUIRED
Component
06.5142.14A
End Cap On board dimmer/FLOS
Control® by Casambi compatible



REQUIRED
Component
06.5142.40A
End Cap On board dimmer/FLOS
Control® by Casambi compatible