

Electrical Feed Rod Rose Ø 50 mm

Designed by Vincent Van Duysen, 2017



Length: 3.94 - Ceiling surface

Adjustable 25 mm, to adapt it to irregular ceilings.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light sources included	no
Number of lamps	1

Physical

Color	Black
Trim	No
Length (in)	3.94
IP internal	20
IP external	20



Download

Family spec sheet	ZIP
Mounting instructions	PDF



Electrical

Emergency type No

Notes

The closure terminals will also be electrified and must be ordered separately. Rod with a Ø50 connection rose: a supply rod for remote installation of the power supply in an accessible place. Adjustable 25 mm, to adapt it to irregular ceilings.

Accessories & Power Supply



REQUIRED
Power supply

LEDSB96W48V-NDM-D01

LED Driver, 48VDC, 96W, Non-Dimming, 120-277V



REQUIRED
Power supply

LEDSB60W48V-NDM-D01

LED Driver, 48VDC, 60W, Non-Dimming, 120-277V



REQUIRED
Power supply

ACCESSORYTYPE1

LEDSB30W48V-NDM-D01

LED power supply source for remote installation, 48V/30W



REQUIRED
Component

06.5135.14A

End Cap Dali/1-10V/FLOS Control® by Casambi compatible



REQUIRED
Component

06.5135.40A

End Cap Dali/1-10V/FLOS Control® by Casambi compatible



REQUIRED
Component

06.5142.14A

End Cap On board dimmer/FLOS Control® by Casambi compatible



REQUIRED
Component

06.5142.40A

End Cap On board dimmer/FLOS Control® by Casambi compatible