

Electrical Feed suspended Rod 27.56" (700mm)

Length: 27.56 - Suspension



Aircraft cable with mounting hardware 33ft (10m). Feed wire 37.8ft (11.5m)

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Suspension
Environments	Indoor dry location

Physical

Color	Black
Length (in)	27.56
Net weight (lb)	1.65
Gross weight (lb)	2.16
Package volume (in)	2380
IP internal	20



Download

Family spec sheet	ZIP
Mounting instructions	PDF



Electrical

Driver Remote

Accessories & Power Supply



REQUIRED
Component

06.5135.14A
End Cap Dali/1-10V/FLOS
Control® by Casambi compatible



REQUIRED
Component

06.5135.40A
End Cap Dali/1-10V/FLOS
Control® by Casambi compatible



REQUIRED
Component

06.5142.14A
End Cap On board dimmer/FLOS
Control® by Casambi compatible



REQUIRED
Component

06.5142.40A
End Cap On board dimmer/FLOS
Control® by Casambi compatible



REQUIRED
Power supply

LEDSB96W48V-NDM-D01
LED Driver, 48VDC, 96W, Non-
Dimming, 120-277V



REQUIRED
Power supply

LEDSB60W48V-NDM-D01
LED Driver, 48VDC, 60W, Non-
Dimming, 120-277V



REQUIRED
Power supply

ACCESSORYTYPE1
LEDSB30W48V-NDM-D01
LED power supply source for
remote installation, 48V/30W