

FLOS

05.4380.OW.78 All Off White

Emi Table


Designed by Erwan Bouroullec, 2023



Anti-glare appliance for installation on tables and coffee tables. Built-in 220-240 V power supply, with cable and plug. Spare parts for the optical module (lens) are available, please see the accessories. Independent control of the Up&Down lighting through Touch Dimming capacitive sensors in the top part of the central rod.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

| | |
|------------------------|---------------------|
| EAN | 8424229003239 |
| Mounting | Table |
| Environments | Indoor dry location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | LED array |
| Lamp category | LED |
| Number of lamps | 1 |
| Power (W) | 37.5 |
| System power (W) | 41 |
| Source flux (lm) | 4174 |
| Lumen Output (lm) | 2959 |

Physical

| | |
|------------------|---------------|
| Colour | All Off White |
| Orientation | Fixed |
| Cord colour | Black |
| Cord length (mm) | 1950 |
| Net weight (kg) | 8.4 |
| IP internal | 20 |

Download

Mounting instructions [↓ PDF](#)

Photometric Files

ULD [↓ ZIP](#)

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Photometric

| | |
|--------------------------|-----------------------|
| Lighting type | Total |
| Light distribution | Symmetric |
| CCT (K) | 2700 |
| CRI> | 90 |
| McAdam steps (SDCM) | 3 |
| Rf fidelity index | 89 |
| Rg gamut index | 101 |
| LED Life / Failure Ratio | L80B50>60.000h_Tc85°C |
| Beam angle C0-180 (°) | 32 |
| Beam angle C90-270 (°) | 32 |
| Extreme cut off | Yes |
| UGR _L | <19 |

Electrical

| | |
|--------------------|-------------------|
| Insulation class | III |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 110-240 |
| LED current (mA) | 760 |
| Power supply | Integrated |
| Dimmable | Yes |
| Dimming range (%) | 1-100 |
| Dimming interface | Dimmer Integrated |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Notes

Gross Luminous Flux:

UpLigh - 3087 lm

DownLight - 1087 lm

Net Luminous Flux:

UpLigh - 2274 lm

DownLight - 685 lm

Accessories & Power Supply



OPTIONAL
Diffuser

Optical

08.0956.14

3 Lens Kit for Emi Ceiling Large,
Emi Floor & Emi Table - Flood
Optic



OPTIONAL
Diffuser

Optical

08.0956.40

3 Lens Kit for Emi Ceiling Large,
Emi Floor & Emi Table - Flood
Optic