

Feed 90° Corner

Designed by FLOS Architectural, 2015




Length: 153 - Suspension

Can be powered. Includes 2 cable suspension kits.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light sources included	no

Physical

Colour	Black
Trim	No
Length (mm)	153
Net weight (kg)	0.76
IP internal	20
IP external	20

Download


Mounting instructions



Electrical


Forward voltage (V)	24
Power supply	Remote excluded
Power supply type	Non Dimmable, Dimmable Casambi, Dimmable DALI 2

Accessories & Power Supply




OPTIONAL
Accessory

08.8883.40A
Canopy surface White, Power
Supply not included order
separately



OPTIONAL
Electrical

08.8886.40
Surface power supply for direct
and indirect lighting with housing
for the driver



OPTIONAL
Electrical

08.8886.40.DA
DALI controller and 24V/185W
equipment to supply and control
both the direct and indirect
lighting, included



OPTIONAL
Installation

08.8887.40A
Endcap. 2 unit kit



OPTIONAL
Electrical

08.8889.40
Recessed power supply rose



OPTIONAL
Power supply
Electrical

60.9352
LED power supply source for
remote installation in 24V/200W
electric control panel. To avoid
problems of overload it is
recommended to install a power
source every 185W. 100/240V.



OPTIONAL
Power supply
Electrical

60.9089
Electronic transformer with
constant voltage (24V) for LED.
100/240V. 60W



OPTIONAL
Power supply
Electrical

60.9407
Electronic transformer with
constant voltage (24V) for LED.
100/240V. 120W