

# FLOS

09.3813.05A Polished Silver

## Find Me 1


Designed by Jorge Herrera, 2018



Accent lighting LED module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module non-dimmable. To individually control the lights, select integrated Casambi versions.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Number of lamps        | 1                   |
| Power (W)              | 5.5                 |
| Source flux (lm)       | 450                 |
| System flux (lm)       | 284                 |
| Efficacy (lm/W)        | 34                  |

### Physical

|                          |                 |
|--------------------------|-----------------|
| Color                    | Polished Silver |
| Trim                     | No              |
| Orientation              | Adjustable      |
| Rotation (°)             | 360             |
| Longitudinal tilting (°) | 90              |
| Length (in)              | 1.3             |
| Net weight (lb)          | 0.25            |
| IP internal              | 20              |

### Download


|                       |       |
|-----------------------|-------|
| Family spec sheet     | ↓ ZIP |
| Mounting instructions | ↓ PDF |

### Photometric Files


|           |       |
|-----------|-------|
| LDT / IES | ↓ ZIP |
|-----------|-------|

### Technical Drawings

|    |       |
|----|-------|
| 2D | ↓ ZIP |
| 3D | ↓ ZIP |



Schematic light drawing



Photometric

|                          |                          |
|--------------------------|--------------------------|
| Lighting type            | Direct                   |
| Light distribution       | Symmetric                |
| CCT (K)                  | 2700                     |
| CRI>                     | 90                       |
| McAdam steps (SDCM)      | 3                        |
| LED Life / Failure Ratio | L80B50>50.000h (Tc=85°C) |
| Beam angle C0-180 (°)    | 20                       |
| Beam angle C90-270 (°)   | 20                       |
| Extreme cut off          | No                       |
| UGR <sub>L</sub>         | <10                      |

Electrical

|                     |                 |
|---------------------|-----------------|
| Insulation class    | III             |
| Forward voltage (V) | 24              |
| LED current (mA)    | 400             |
| Driver              | Remote excluded |
| Dimmable            | No              |
| Dimming type        | Non Dimmable    |

Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Notes

Accessories included (honeycomb and screening crosspiece).