

## Find Me 1 Adressable

Designed by Jorge Herrera, 2026



LED accent lighting module for installation in the The Micro Running Magnet Pro system. Integrated DC/DC electronic converter. "Addressable" version, with individual control of up to 3 addresses or groups.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Number of lamps        | 1                   |
| Power (W)              | 4.8                 |
| System power (W)       | 5.5                 |
| Source flux (lm)       | 463                 |
| Lumen Output (lm)      | 289                 |
| Efficacy (lm/W)        | 35                  |

### Physical

|                          |            |
|--------------------------|------------|
| Colour                   | White      |
| Orientation              | Adjustable |
| Rotation (°)             | 360        |
| Longitudinal tilting (°) | 90         |
| Spot diameter (mm)       | 33         |
| Length (mm)              | 41         |
| Net weight (kg)          | 0.11       |
| IP internal              | 20         |

### Drawing Thumbnail

Download

Mounting instructions

ZIP

Photometric Files

LDT / IES

ZIP

Technical Drawings

2D

ZIP

3D

ZIP

Ecodesign and Energy Labelling


This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Schematic light drawing



Photometric

|                          |                            |
|--------------------------|----------------------------|
| Lighting type            | Direct                     |
| Light distribution       | Symmetric                  |
| CCT (K)                  | 3000                       |
| CRI>                     | 90                         |
| McAdam steps (SDCM)      | 3                          |
| Rf fidelity index        | 91                         |
| Rg gamut index           | 98                         |
| LED Life / Failure Ratio | L95B11 > 50.000h (Tc=85°C) |
| Beam angle C0-180 (°)    | 20                         |
| Beam angle C90-270 (°)   | 20                         |
| Extreme cut off          | No                         |
| UGR <sub>L</sub>         | <10                        |

Electrical

|                     |                 |
|---------------------|-----------------|
| Insulation class    | III             |
| Forward voltage (V) | 24              |
| LED current (mA)    | 400             |
| Power supply        | Remote excluded |
| Dimmable            | Yes             |
| Dimming range (%)   | 1-100           |

Notes

Accessories included (honeycomb and screening crosspiece). The control system for the Casambi version of the light fixtures is directly and individually regulated wirelessly using the FLOS Control® powered by Casambi application. Other types of regulation operate in broadcast mode (all lights are regulated at the same time). The Casambi module is integrated within the fixture and works with a 24V non-dimmable power supply connected directly to the track.