

FLOS

09.3710.05C9S Polished Silver

Find Me 1 Suspension

Designed by Jorge Herrera

LED - Power LED - 6W - 365lm - 3000K - CRI> 90 - Beam° 14

The Find Me Suspension is a thin pendant mount fixture. Deep matte black snoot maximizes cut off and reduces glare. Snoot in pendant version can be changed out to add a touch of color. The Find Me line is available as a single and as a pendant.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Power (W)	6
System flux (lm)	365

Physical

Color	Polished Silver
Trim	No
Orientation	Adjustable
Net weight (lb)	0.51
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	---------------------

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Ecodesign and Energy Labelling




Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	14
Beam angle C90-270 (°)	14
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	12
LED current (mA)	500
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable Casambi, Mains Cut Dimming, Dimmable 0-10V, Dimmable DALI 2


Accessories & Power Supply



REQUIRED
Power supply


Electrical

SP40W500MA-10V-A02
Splice Box 40W, 1% dim, 0-10V,
500mA 120/277V.




REQUIRED
Accessory

08U0003.14
Find Me Suspensión Cover Plate
Canopy, Black



REQUIRED
Accessory


08U0003.30
Find Me Suspensión Cover Plate
Canopy, White



REQUIRED
Power supply

Electrical


SP25W500MA-10V-A01
Splice Box UL 7"x3-5/8"x1-1/4",
500mA , 25W, 0-10V Dimmable,
120-277V



REQUIRED
Power supply

Electrical


SP30W500MA-ELV-U01
Splice Box UL 7"x3-5/8"x1-1/4",
500mA , 30W, ELV Dimmable,
120-277V



REQUIRED
Power supply

Electrical

SP14W500MA-TRI-S01
Splice Box UL 7"x3-5/8"x1-1/4",
Dim Hi-lume 1% 2-Wire LED
Driver 500mA , 14W, 120V



REQUIRED
Power supply

Electrical

SP26W500MA-TRI-S01
Splice Box UL 7"x3-5/8"x1-1/4",
Dim Hi-lume 1% 2-Wire LED
Driver 500mA , 26W, 120V