

FLOS

09.3711.30C9S White

Find Me 1 Suspension


Designed by Jorge Herrera



The Find Me Suspension is a thin pendant mount fixture. Deep matte black snoot maximizes cut off and reduces glare. Snoot in pendant version can be changed out to add a touch of color. The Find Me line is available as a single and as a pendant.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	6
System flux (lm)	344

Physical


Color	White
Trim	No
Orientation	Adjustable
Net weight (lb)	0.51
Package volume (in)	62
IP internal	20

Download


[Family spec sheet](#)  ZIP

[Mounting instructions](#)  PDF

Photometric Files


[LDT / IES](#)  ZIP

Ecodesign and Energy Labelling

   Replaceable (LED only) light source by a professional



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	14
Beam angle C90-270 (°)	14
UGR _L	<10


Electrical

Insulation class	III
Forward voltage (V)	12
LED current (mA)	500
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable DALI 2, Dimmable 0-10V, Dimmable Casambi, Mains Cut Dimming

Notes

Integral LED is not field replaceable. Fixture is constant Current Low Voltage LED, Class 2. Just 1 accessory can be installed at the time. For filter options contact Flos. Wiring suitable for plenum spaces. The fitting is supplied pre-wired ready to be connected to a remote power supply (not included). The product includes interchangeable shield cylinder in different colours (orange, violet and black) 3500K available, but not cataloged. Consult factory for additional color temperatures.

Accessories & Power Supply




REQUIRED
Power supply

Electrical

SP40W500MA-10V-A02

Splice Box 40W, 1% dim, 0-10V, 500mA 120/277V.




REQUIRED
Power supply

Electrical

SP25W500MA-10V-A01

Splice Box UL 7"x3-5/8"x1-1/4", 500mA , 25W, 0-10V Dimmable, 120-277V




REQUIRED
Power supply

Electrical

SP30W500MA-ELV-U01

Splice Box UL 7"x3-5/8"x1-1/4", 500mA , 30W, ELV Dimmable, 120-277V




REQUIRED
Power supply

Electrical

SP14W500MA-TRI-S01

Splice Box UL 7"x3-5/8"x1-1/4", Dim Hi-lume 1% 2-Wire LED Driver 500mA , 14W, 120V




REQUIRED
Power supply

Electrical

SP26W500MA-TRI-S01


Splice Box UL 7"x3-5/8"x1-1/4", Dim Hi-lume 1% 2-Wire LED Driver 500mA , 26W, 120V



REQUIRED
Accessory

08U0003.14

Find Me Suspensión Cover Plate Canopy, Black



REQUIRED
Accessory

08U0003.30

Find Me Suspensión Cover Plate Canopy, White