

# FLOS

05.5136.14.CB Black

## Find Me 1 Suspension Casambi Dimmable

Designed by FLOS Architectural, 2023


5.5W - 193lm - 3000K - CRI> 90 - Beam° 20



LED projection lighting module for installation in the Zero Track Pro system.  
Electronic DC/DC converter incorporated. Individual wireless adjustment via Casambi.  
Casambi control implemented via the FLOS Control® app for mobile devices  
(available in the Apple Store and Google Play). Cannot be installed on vertical tracks.  
Accessories included (honeycomb grid and protection bar).

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Number of lamps        | 1                   |
| Power (W)              | 5.5                 |
| Source flux (lm)       | 446                 |
| System flux (lm)       | 193                 |
| Efficacy (lm/W)        | 36                  |

### Physical

|             |       |
|-------------|-------|
| Color       | Black |
| Orientation | Fixed |
| IP internal | 20    |

### Download

|                       |     |
|-----------------------|-----|
| Family spec sheet     | ZIP |
| Mounting instructions | PDF |

### Photometric Files


|           |     |
|-----------|-----|
| LDT / IES | ZIP |
|-----------|-----|

### Technical Drawings

|    |     |
|----|-----|
| 2D | ZIP |
| 3D | ZIP |



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 3000      |
| CRI>                   | 90        |
| McAdam steps (SDCM)    | 2         |
| Beam angle C0-180 (°)  | 20        |
| Beam angle C90-270 (°) | 20        |
| UGR <sub>L</sub>       | <10       |

Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Insulation class    | III                                   |
| Forward voltage (V) | 24                                    |
| LED current (mA)    | 400                                   |
| Driver              | Remote excluded                       |
| Dimmable            | Yes                                   |
| Dimming type        | Dimmable Casambi                      |
| Dimming range (%)   | 1-100                                 |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

Non-replaceable light source

Replaceable control gear by a professional