



05.5130.ES.DA Brushed Bronze

Find Me 1 Suspension Dali Dimmable

Designed by FLOS Architectural, 2023

5.5W - 309lm - 2700K - CRI> 90 - Beam° 14

LED projection lighting module for installation in the Zero Track Pro system.
Electronic DC/DC converter incorporated. Individual wireless adjustment via Casambi.
Casambi control implemented via the FLOS Control® app for mobile devices
(available in the Apple Store and Google Play). Cannot be installed on vertical tracks.
Accessories included (honeycomb grid and protection bar).

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	5.5
Source flux (lm)	432
System flux (lm)	309

Physical

Color	Brushed Bronze
Orientation	Fixed
IP internal	20



Download

Family spec sheet [ZIP](#)
Mounting instructions [PDF](#)

Photometric Files


LDT / IES [ZIP](#)

Technical Drawings

2D [ZIP](#)
3D [ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	2
Beam angle C0-180 (°)	14
Beam angle C90-270 (°)	14
Extreme cut off	No
UGR _L	<10

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	400
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable DALI 2
Dimming interface	Remote Dimmable (Dimmer Not Included)

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Non-replaceable light source



Replaceable control gear by a professional