

# FLOS

03.6272.14D Black

## Find Me 1 Suspension On Board Dimmer


Designed by FLOS Architectural, 2016



Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 8                   |
| System power (W)       | 8.4                 |
| Lumen Output (lm)      | 344                 |
| Efficacy (lm/W)        | 40.95               |

### Physical

|                 |       |
|-----------------|-------|
| Colour          | Black |
| Trim            | No    |
| Orientation     | Fixed |
| Length (mm)     | 130   |
| Net weight (kg) | 0.3   |
| IP internal     | 20    |
| IP external     | 20    |

### Download

[Mounting instructions](#) PDF

[Item information](#) JPG

### Photometric Files

[LDT / IES](#) ZIP

### Technical Drawings


[2D](#) ZIP

[3D](#) ZIP

[Bim](#) ZIP



## Schematic light drawing



### Photometric

|                          |                               |
|--------------------------|-------------------------------|
| Lighting type            | Direct                        |
| Light distribution       | Symmetric                     |
| CCT (K)                  | 2700                          |
| CRI>                     | 90                            |
| McAdam steps (SDCM)      | 3                             |
| LED Life / Failure Ratio | L80B50 > 50.000h<br>(Tc=85°C) |
| Beam angle C0-180 (°)    | 14                            |
| Beam angle C90-270 (°)   | 14                            |
| UGR <sub>L</sub>         | <10                           |

### Electrical

|                     |                 |
|---------------------|-----------------|
| Insulation class    | III             |
| Forward voltage (V) | 24              |
| Power supply        | Remote excluded |
| Dimmable            | Yes             |
| Power supply type   | Dimmer on board |
| Dimming range (%)   | 20-100          |

### Notes

Maximum 21 spots for a single driver. For wireless lighting control, choose integrated Casambi versions.