

FLOS

05.5121.ER.1V Brushed Steel

Find Me 2 1-10V Dimmable

Designed by FLOS Architectural, 2023


10.5W - 441lm - 2700K - CRI> 90 - Beam° 19



LED projection lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual wireless adjustment via Casambi. Casambi control implemented via the FLOS Control® app for mobile devices (available in the Apple Store and Google Play). Accessories included (honeycomb grid and protection bar).

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|---------------------|
| Mounting | Track |
| Environments | Indoor dry location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Power LED |
| Number of lamps | 1 |
| Power (W) | 10.5 |
| Source flux (lm) | 724 |
| Lumen Output (lm) | 441 |

Physical

| | |
|--------------------------|---------------|
| Colour | Brushed Steel |
| Orientation | Adjustable |
| Rotation (°) | 360 |
| Longitudinal tilting (°) | 90 |
| Net weight (kg) | 0.3 |
| IP internal | 20 |

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Beam Angle: 19°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 1989 | 0.34 |
| 2 | 497 | 0.67 |
| 3 | 221 | 1.01 |
| 4 | 124 | 1.34 |
| 5 | 80 | 1.68 |

Luminous flux luminaire
441 lm

Photometric

| | |
|------------------------|-----------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 2700 |
| CRI> | 90 |
| McAdam steps (SDCM) | 2 |
| Beam angle C0-180 (°) | 19 |
| Beam angle C90-270 (°) | 19 |
| Extreme cut off | No |
| UGR _L | <10 |

Electrical

| | |
|---------------------|---------------------------------------|
| Insulation class | III |
| Forward voltage (V) | 24 |
| LED current (mA) | 760 |
| Power supply | Remote excluded |
| Dimmable | Yes |
| Power supply type | Dimmable 1-10V |
| Dimming interface | Remote Dimmable (Dimmer Not Included) |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Non-replaceable light source



Replaceable control gear by a professional