FLOS

FU234030 Black

# Flauta H225 Riga

Designed by Patricia Urquiola, 2020

12W - 493lm - 2700K - CRI> 95

Inspired by the shapes of organs and flutes, Flauta's dual spotlights stand out thanks to a small circular reflector that captures and reverberates the light emitted. The cylindrical body are characterized by the surface etching in two refined variations: Flauta Riga, with vertical lines, and Flauta Spiga, characterized by an elegant and sophisticated herringbone pattern. The wall sconces comes in three different heights, two surface textures, and a total of nine* finishes, providing various personalization possibilities. Details Indoor only - 2700K Up and down lighting Integral LED driver 12W Delivered lumens : 2x347lm ADA compliant Finishes Flauta Indoor Only - anodized blue steel, anodized copper, anodized ruby red, black and white Flauta Indoor/Outdoor - anthracite, black, dark brown, forest green, grey, and white "The Flauta collection meets a desire for the creation of an adaptable, changing project, ideal for contract or residential environments, both indoor and outdoor." - Patricia Urquiola Please note that all fixtures include a circular backplate, not always shown in the images.




Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

## Download

Mounting instructions ZIP

## Main specifications

| | |
|---|---|
| EAN | 8059607001844 |
| Mounting | Wall |
| Environments | Indoor dry location |
| Light Source Type | LED |
| Light sources included | Yes |
| LED type | LED Module |
| Power (W) | 12 |
| System power (W) | 12 |
| Source flux (lm) | 493lm |
| System flux (lm) | 493 |

## Physical

| | |
|---|---|
| Color | Black |
| Net weight (lb) | 1.76 |
| Gross weight (lb) | 2.87 |
| Package volume (in) | 437.48 |
| IP internal | 40 |
| IP external | 40 |

## Photometric

| | |
|---|---|
| Lighting type | Direct, Indirect |
| Light distribution | Asymmetric |
| CCT (K) | 2700 |
| CRI> | 95 |
| Extreme cut off | No |

## Electrical

| | |
|---|---|
| Insulation class | II |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220-240 |
| Driver | Integrated |
| Dimming type | Dimmable DALI 1, Dimmable Push |
| Dimming interface | Dimmer Integrated |
| Batteries inside | No |