

# FLOS

09.2110.05C Polished Aluminium

## Fort Knox Wall LED Dimmable 1-10V

Designed by Philippe Starck, 2018




LED - Power LED - 30.7W - 3036lm - 3000K - CRI> 90 - Beam° 29

Wall-mounted LED luminaire for indirect lighting. Power source incorporated into luminaire's body.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

EAN	8424229006353
Mounting	Wall surface
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	30.7
System power (W)	35
Source flux (lm)	3900
Lumen Output (lm)	3036

### Physical

Colour	Polished Aluminium
Trim	No
Orientation	Fixed
Length (mm)	200
Net weight (kg)	1.4
IP internal	20

### Download

[Mounting instructions](#)  PDF

### Photometric Files

[LDT / IES](#)  ZIP

### Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



## Schematic light drawing



## Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L80B50 50.000h
Beam angle C0-180 (°)	29
Beam angle C90-270 (°)	86
Extreme cut off	No
UGR <sub>L</sub>	<10

## Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable 1-10V

## Ecodesign and Energy

### Labelling

