

## Franco 2 CoB Led Asymmetric Optic

Designed by FLOS Outdoor, 2007



43W - 2919lm - 4000K - CRI> 80

LED source included. Integrated electrical power supply 220-240V ON/OFF. Graduated fixing bracket included. Equipped with a M20x1.5 cable guide (for 7mm<ø<13mm cables) and IP68 connector. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use. Optional accessories: posts and arms for mast mounting.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                        |               |
|------------------------|---------------|
| EAN                    | 8054793698656 |
| Mounting               | Ground        |
| Light source type      | LED           |
| Light sources included | Yes           |
| LED type               | LED array     |
| Number of lamps        | 1             |
| Power (W)              | 43            |
| System power (W)       | 43            |
| Source flux (lm)       | 5560          |
| Lumen Output (lm)      | 2919          |

### Physical

|                          |            |
|--------------------------|------------|
| Colour                   | White      |
| Orientation              | Adjustable |
| Longitudinal tilting (°) | 113        |
| Net weight (kg)          | 4.22       |
| Package height (mm)      | 145        |
| Package width (mm)       | 260        |
| Package length (mm)      | 430        |
| Package volume (m3)      | 0.02       |
| IP internal              | 65         |
| Dynamic load (kg)        | No         |

### Download

Mounting instructions  ZIP

### Photometric Files

LDT / IES  ZIP

### Technical Drawings

2D  ZIP

3D  ZIP

### Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D




REPLACEABLE2



PWRSUPRPL2



Schematic light drawing



Photometric

|                    |            |
|--------------------|------------|
| Lighting type      | Direct     |
| Light distribution | Asymmetric |
| CCT (K)            | 4000       |
| CRI>               | 80         |
| Extreme cut off    | No         |

Electrical

|                    |              |
|--------------------|--------------|
| Insulation class   | I            |
| Frequency (Hz)     | 50/60        |
| Main voltage (Vac) | 220-240      |
| Power supply       | Integrated   |
| Dimmable           | No           |
| Power supply type  | Non Dimmable |
| Dimming interface  | Not Dimmable |
| Emergency          | No           |

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply




OPTIONAL  
Bracket

FA9533  
Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 180 mm Double



OPTIONAL  
Pole

FA24806  
Pole Ø76 mm h 3500 mm(with  
Base)



OPTIONAL  
Accessory

F990E00A000  
S.P.D. (SURGE PROTECTION  
DEVICE)



OPTIONAL  
Pole

FA24833  
Pole Ø76 mm h 3500 mm(with  
Base)



OPTIONAL  
Pole

FA25006  
Pole Ø76 mm h 3500 mm (+500  
mm In-ground)



OPTIONAL  
Pole

FA25033  
Pole Ø76 mm h 3500 mm (+500  
mm In-ground)



OPTIONAL  
Pole

FA414506  
Pole Ø 102 mm h 4000 mm (+500  
mm In-ground)



OPTIONAL  
Bracket

FA11506  
Pole Bracket Franco 2/Perseo 4 Ø  
76 mm 500 mm Double



OPTIONAL  
Accessory

FA116

Base Plate and Fixing Bolts for  
Pole Ø 102 mm h 4000/5000 mm  
with Base



OPTIONAL  
Bracket

FA8906

Pole Bracket Franco 2/Perseo 4 Ø  
102 mm 500 mm Double



OPTIONAL  
Bracket

FA11233

Pole Bracket Franco 2/Perseo 4 Ø  
76 mm 180 mm Single



OPTIONAL  
Bracket

FA7933

Pole Bracket Franco 2/Perseo 4 Ø  
102 mm 500 mm Single



OPTIONAL  
Bracket

FA7833

Pole Bracket Franco 2/Perseo 4 Ø  
102 mm 180 mm Single



OPTIONAL  
Bracket

FA9506

Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 180 mm Double



OPTIONAL  
Pole

FA24906

Pole Ø76 mm h 4500 mm(with  
Base)



OPTIONAL  
Bracket

FA8933

Pole Bracket Franco 2/Perseo 4 Ø  
102 mm 500 mm Double



OPTIONAL  
Bracket

FA7806

Pole Bracket Franco 2/Perseo 4 Ø  
102 mm 180 mm Single



OPTIONAL  
Bracket

FA7906

Pole Bracket Franco 2/Perseo 4 Ø  
102 mm 500 mm Single



OPTIONAL  
Pole

FA415033

Pole Ø 102 mm h 5000 mm With  
Base



OPTIONAL  
Bracket

FA11306

Pole Bracket Franco 2/Perseo 4 Ø  
76 mm 500 mm Single



OPTIONAL  
Pole

FA414533

Pole Ø 102 mm h 4000 mm (+500  
mm In-ground)



OPTIONAL  
Bracket

FA9433

Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 500 mm



OPTIONAL  
Pole

FA415506

Pole Ø 102 mm h 5000 mm (+500  
mm In-ground)



OPTIONAL  
Bracket

FA9606

Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 500 mm Double



OPTIONAL  
Bracket

FA11533

Pole Bracket Franco 2/Perseo 4 Ø  
76 mm 500 mm Double



OPTIONAL  
Bracket

FA9633

Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 500 mm Double



OPTIONAL  
Bracket

FA9033

Pole Bracket Franco 2/Perseo 4 Ø  
102 mm 180 mm Double



OPTIONAL  
Pole

FA415006

Pole Ø 102 mm h 5000 mm With  
Base



OPTIONAL  
Pole

FA24933

Pole Ø 76 mm h 4500 mm(with  
Base)



OPTIONAL  
Pole

FA25106

Pole Ø 76 mm h 4500 mm (+500  
mm In-ground)



OPTIONAL  
Bracket

FA11206

Pole Bracket Franco 2/Perseo 4 Ø  
76 mm 180 mm Single



OPTIONAL  
Pole

FA25133

Pole Ø 76 mm h 4500 mm (+500  
mm In-ground)



OPTIONAL  
Bracket

FA9006

Pole Bracket Franco 2/Perseo 4 Ø  
102 mm 180 mm Double



OPTIONAL  
Bracket

FA11333

Pole Bracket Franco 2/Perseo 4 Ø  
76 mm 500 mm Single



OPTIONAL  
Pole

FA414006

Pole Ø 102 mm h 4000 mm With  
Base



OPTIONAL  
Bracket

FA9333

Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 180 mm



OPTIONAL  
Bracket

FA9306

Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 180 mm



OPTIONAL  
Bracket

FA11433

Pole Bracket Franco 2/Perseo 4 Ø  
76 mm 180 mm Double



OPTIONAL  
Bracket

FA9406

Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 500 mm



OPTIONAL  
Bracket

FA11406

Pole Bracket Franco 2/Perseo 4 Ø  
76 mm 180 mm Double



## OPTIONAL Pole

FA414033

Pole Ø 102 mm h 4000 mm With  
Base