

Franco 2 CoB Led Symmetric Optic

Designed by FLOS Outdoor, 2007



43W - 3380lm - 3000K - CRI> 80 - Beam° 80

LED source included. Integrated electrical power supply 220-240V ON/OFF. Graduated fixing bracket included. Equipped with a M20x1.5 cable guide (for 7mm<ø<13mm cables) and IP68 connector. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use. Optional accessories: posts and arms for mast mounting.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

EAN	8054793698939
Mounting	Ground
Light source type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
Power (W)	43
System power (W)	43
Source flux (lm)	5423
Lumen Output (lm)	3380

Physical

Colour	Grey
Orientation	Adjustable
Longitudinal tilting (°)	113
Net weight (kg)	4.22
Package height (mm)	145
Package width (mm)	260
Package length (mm)	430
Package volume (m3)	0.02
IP internal	65
Dynamic load (kg)	No

Download

Mounting instructions [ZIP](#)

Photometric Files

LDT / IES [ZIP](#)

Technical Drawings

2D [ZIP](#)
3D [ZIP](#)

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D




REPLACEABLE2



PWRSUPRPL2



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	80
Beam angle C90-270 (°)	80
Extreme cut off	No


Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL
Accessory

F990E00A000
S.P.D. (SURGE PROTECTION
DEVICE)



OPTIONAL
Pole

FA24806
Pole Ø76 mm h 3500 mm(with
Base)



OPTIONAL
Pole

FA25006
Pole Ø76 mm h 3500 mm (+500
mm In-ground)



OPTIONAL
Pole

FA24906
Pole Ø76 mm h 4500 mm(with
Base)



OPTIONAL
Pole

FA25106
Pole Ø76 mm h 4500 mm (+500
mm In-ground)



OPTIONAL
Pole

FA414006
Pole Ø 102 mm h 4000 mm With
Base



OPTIONAL
Pole

FA414506
Pole Ø 102 mm h 4000 mm (+500
mm In-ground)



OPTIONAL
Bracket

FA11206
Pole Bracket Franco 2/Perseo 4 Ø
76 mm 180 mm Single



OPTIONAL
Bracket

FA7806

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 180 mm Single



OPTIONAL
Pole

FA415006

Pole Ø 102 mm h 5000 mm With
Base



OPTIONAL
Bracket

FA11406

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 180 mm Double



OPTIONAL
Bracket

FA9606

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 500 mm Double



OPTIONAL
Bracket

FA7906

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 500 mm Single



OPTIONAL
Pole

FA415506

Pole Ø 102 mm h 5000 mm (+500
mm In-ground)



OPTIONAL
Bracket

FA9506

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 180 mm Double



OPTIONAL
Bracket

FA11306

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 500 mm Single



OPTIONAL
Bracket

FA9406

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 500 mm



OPTIONAL
Accessory

FA116

Base Plate and Fixing Bolts for
Pole Ø 102 mm h 4000/5000 mm
with Base



OPTIONAL
Bracket

FA11506

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 500 mm Double



OPTIONAL
Bracket

FA9306

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 180 mm



OPTIONAL
Bracket

FA9006

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 180 mm Double



OPTIONAL
Bracket

FA8906

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 500 mm Double