


FLOS

FA972841333.A Anthracite

Franco 3 CoB Led Symmetric Optic

Designed by FLOS Outdoor, 2007



LED source included. Integrated electrical power supply 220-240V ON/OFF. Graduated fixing bracket included. Equipped with a M20x1.5 cable guide (for 7mmϕ<math><13\text{mm}</math> cables) and IP68 connector. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use. Optional accessories: posts and arms for mast mounting.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8054793700939
Mounting	Ground
Light source type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
Power (W)	52
System power (W)	52
Source flux (lm)	6446
Lumen Output (lm)	4142

Physical

Colour	Anthracite
Orientation	Adjustable
Longitudinal tilting (°)	117
Net weight (kg)	6.03
Package height (mm)	170
Package width (mm)	305
Package length (mm)	505
Package volume (m3)	0.03
IP internal	65
Drive Over	No

Download

[Mounting instructions](#)  ZIP

Photometric Files

[LDT / IES](#)  ZIP


Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



Schematic light drawing



Beam Angle: 95°

h(m)	E(lx)	D(m)
1	2282	2.22
2	570	4.45
3	254	6.67
4	143	8.90
5	91	11.12

Luminous flux luminaire
4142 lm

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	95
Beam angle C90-270 (°)	86
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL
Accessory

F990E00A000

S.P.D. (SURGE PROTECTION
DEVICE)



OPTIONAL
Pole

FA24833

Pole Ø76 mm h 3500 mm (with
Base)



OPTIONAL
Pole

FA25033

Pole Ø76 mm h 3500 mm (+500
mm In-ground)



OPTIONAL
Bracket

FA9633

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 500 mm Double



OPTIONAL
Bracket

FA9433

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 500 mm



OPTIONAL
Pole

FA24933

Pole Ø76 mm h 4500 mm (with
Base)



OPTIONAL
Pole

FA25133

Pole Ø76 mm h 4500 mm (+500
mm In-ground)



OPTIONAL
Pole

FA414033

Pole Ø 102 mm h 4000 mm With
Base



OPTIONAL Pole

FA414533

Pole Ø 102 mm h 4000 mm (+500 mm In-ground)



OPTIONAL Bracket

FA11433

Pole Bracket Franco 2/Perseo 4 Ø 76 mm 180 mm Double



OPTIONAL Bracket

FA8933

Pole Bracket Franco 2/Perseo 4 Ø 102 mm 500 mm Double



OPTIONAL Bracket

FA11533

Pole Bracket Franco 2/Perseo 4 Ø 76 mm 500 mm Double



OPTIONAL Bracket

FA9333

Pole Bracket Franco 2/Perseo 4 Ø 60 mm 180 mm



OPTIONAL Bracket

FA7933

Pole Bracket Franco 2/Perseo 4 Ø 102 mm 500 mm Single



OPTIONAL Pole

FA415033

Pole Ø 102 mm h 5000 mm With Base



OPTIONAL Accessory

FA116

Base Plate and Fixing Bolts for Pole Ø 102 mm h 4000/5000 mm with Base



OPTIONAL
Bracket

FA9033

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 180 mm Double



OPTIONAL
Bracket

FA11233

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 180 mm Single



OPTIONAL
Bracket

FA9533

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 180 mm Double



OPTIONAL
Bracket

FA11333

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 500 mm Single



OPTIONAL
Bracket

FA7833

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 180 mm Single