

G-O IN

Designed by Jorge Herrera, 2017




LED - Top LED - 1.2W - 3000K - Beam° 111

Recessed sign luminaire for indoor application. Power supply source not included: electronic transformer with constant voltage (24V) for LED. 220/240V, 50/60Hz. It includes 1000mm power supply cable.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Wall recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Power (W)	1.2
Source flux (lm)	105

Physical

Colour	Lighting amber
Trim	No
Orientation	Fixed
Net weight (kg)	0.7
IP internal	20
IP external	20

Download

Mounting instructions

PDF



Photometric

Lighting type	Direct, Indirect
Light distribution	Symmetric
CCT (K)	3000
LED Life / Failure Ratio	L80B10 > 50.000h
Beam angle C0-180 (°)	111
Beam angle C90-270 (°)	111
UGRL	<10

Electrical

Forward voltage (V)	24
Power supply	Remote excluded
Dimmable	No
Power supply type	Non Dimmable
Emergency	No

Accessories & Power Supply



REQUIRED
Power supply

ACCESSORYTYPE1

60.9157
Electronic transformer with
constant voltage (24V) for LED.
8W, 110/240V, 50/60H



REQUIRED
Power supply

ACCESSORYTYPE1

60.8703
Electronic transformer with
constant voltage (24V) for LED.
100/240V, 25W



REQUIRED
Accessory

ACCESSORYTYPE1

60.9766
Control Unit DALI



REQUIRED
Accessory

ACCESSORYTYPE1

60.8640
Control Unit 1-10V



OPTIONAL
Power supply

ACCESSORYTYPE1

60.8079
Electronic transformer with
constant voltage (24V) for LED.
8W, 220/240V, 50/60H