

# FLOS

09.3200.ANA9S Anodized Black

## G-O White Light


Designed by Jorge Herrera

LED - Top LED - 1.2W - 4lm - 3000K - CRI> 90 - Beam° 74

G-O is a family of small lights that make a big impression while providing useful illumination for stairs, paths and way finding, while only using 1.2 watts per fixture. Robust machined bronze, stainless steel or aluminum construction available in a variety of finishes and light color options result in a lighting tool that enhances the most refined architecture.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Wall recessed       |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Top LED             |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 1.2                 |
| Source flux (lm)       | 96                  |
| System flux (lm)       | 4                   |

### Physical

|                     |                |
|---------------------|----------------|
| Color               | Anodized Black |
| Trim                | Yes            |
| Orientation         | Fixed          |
| Recessed depth (in) | 2.2            |
| Net weight (lb)     | 0.25           |
| Gross weight (lb)   | 0.36           |
| Package volume (in) | 62             |
| IP internal         | 65             |

### Download


|                       |     |
|-----------------------|-----|
| Family spec sheet     | ZIP |
| Mounting instructions | PDF |

### Photometric Files

|           |     |
|-----------|-----|
| LDT / IES | ZIP |
|-----------|-----|



Schematic light drawing



Photometric

|                          |                  |
|--------------------------|------------------|
| Lighting type            | Direct, Indirect |
| Light distribution       | Symmetric        |
| CCT (K)                  | 3000             |
| CRI>                     | 90               |
| LED Life / Failure Ratio | L80B10 > 50.000h |
| Beam angle C0-180 (°)    | 74               |
| Beam angle C90-270 (°)   | 74               |
| Extreme cut off          | No               |
| UGRL                     | <16              |


Electrical

|                     |                 |
|---------------------|-----------------|
| Insulation class    | III             |
| Forward voltage (V) | 24              |
| LED current (mA)    | 25              |
| Driver              | Remote excluded |

Notes

Optional extruded aluminum accessory for embedding in concrete walls installations available. Fixture can be wired in paralel, up to maximum allowed wattage of power supply Distance should not exceed driver’s limits for voltage drop.

Accessories & Power Supply




REQUIRED  
Power supply

LEDSB30W24V-10V-D1  
LED Driver, 30W, 120-277Vac, 0-10V dimming driver



OPTIONAL  
Accessory

08.8422.00  
Prepared for recessing



OPTIONAL  
Power supply

LEDSB60W24V-VAR-Y1  
LED Driver, 24VDC, 60W, Variable dim Triac, 0-10V Dimming PWM, 120-277Vac , indoor-outdoor enclosure