

FLOS

FA50703501 White

Heavy Metal Hp Wall 2 Mono

Designed by FLOS Outdoor, 2011




3W - 218lm - 2700K - CRI> 80 - Beam° 36

LED source included. Electric remote 24V dc ON/OFF power supply to be ordered separately. Wall fixing bracket included. The luminaire is equipped with a protruding, neoprene, 250 mm cable and a wiring kit with crimp connectors and adhesive heat-shrink tubing guaranteeing the water tightness of the connection. Extra clear transparent glass.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793624570
Mounting	Wall
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	3
System power (W)	4.5
Source flux (lm)	331
Lumen Output (lm)	218

Physical

Colour	White
Orientation	Fixed
Net weight (kg)	0.48
Package height (mm)	134
Package width (mm)	70
Package length (mm)	83
IP internal	65

Download

Mounting instructions  ZIP

Photometric Files

LDT / IES  ZIP

Technical Drawings


2D  ZIP

3D  ZIP




Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F

 Non-replaceable light source

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	36
Beam angle C90-270 (°)	36
Extreme cut off	No

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	24
Power supply	Remote excluded
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL
Power supply

F990B27A000
Power supply 24Vdc 70W / 220-240V IP67 Class I selv. Non Dimmable



OPTIONAL
Power supply

F990B28A000
Power supply 24Vdc 50W / 220-240V IP67 Class I selv. Non Dimmable



OPTIONAL

F990B34A000
Power Supply dual function C.V.
Vout 24Vdc 8W, Vin 220÷240V
C.C. Iout 350mA: 8W, Vin 220÷240V IP 20 Class II Selv. NON Dimmable



OPTIONAL
Power supply

RF25747
Power supply 24V 10W /110-240V IP20 Class II selv. Non Dimmable



OPTIONAL
Power supply

RF25748
Power Supply dual function C.V.
Vout 24Vdc 8W, Vin 220÷240V
C.C. Iout 350mA: 8W, Vin 220÷240V IP 65 Class II Selv. NON Dimmable



OPTIONAL
Power supply

RF25757
Power supply 24V 10W / 110-240V IP67 Class II selv._Non Dimmable