

FLOS



F012A02C037.A Burgundy Red/Black Lava

IC F1 Outdoor H 1350 mm


Designed by Michael Anastassiades, 2019



Bulb not included. 5-m cable with Schuko IP44 plug suitable for outdoor use. Backlit floor dimmer switch on the IP65 cable enables ON/OFF function and brightness regulation 30-100% (with dimmable LED bulb).

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793218083
Mounting	Floor
Environments	Outdoor wet location
Light source type	Bulb
Light sources included	No
Number of lamps	1

Physical

Colour	Burgundy Red/Black Lava
Trim	No
Orientation	Fixed
Net weight (kg)	12.99
IP internal	65

Download

Mounting instructions  ZIP

Photometric Files

LDT / IES  ZIP

Technical Drawings


2D  ZIP

3D  ZIP

 Bim  ZIP



Schematic light drawing



Ecodesign and Energy Labelling



Replaceable (LED only)
light source by an end-user

Photometric

Lighting type	Direct
Light distribution	Symmetric
Extreme cut off	No

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Remote included
Dimmable	Yes
Power supply type	Dimmer on board
Dimming interface	Switch Integrated (Remote Dimmable)
Emergency	No

Notes

Bulb not included. LED: max 8W - E14



Bulbs



NOT INCLUDED

RF32290

LED Lamp E14 8W 2700K T28



NOT INCLUDED

RF32291

LED Lamp E14 8W 3000K T28