

# FLOS



F012A03C059.A Brass Finish/Grey Lava

## IC F1 Outdoor H 1350 mm


Designed by Michael Anastassiades, 2019



Bulb not included. 5-m cable with Schuko IP44 plug suitable for outdoor use. Backlit floor dimmer switch on the IP65 cable enables ON/OFF function and brightness regulation 30-100% (with dimmable LED bulb).

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

EAN	8054793218564
Mounting	Floor
Environments	Outdoor wet location
Light source type	Bulb
Light sources included	No
Number of lamps	1

### Physical

Colour	Brass Finish/Grey Lava
Trim	No
Orientation	Fixed
Net weight (kg)	12.65
IP internal	65

### Download

[Mounting instructions](#)  ZIP

### Photometric Files

[LDT / IES](#)  ZIP

### Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



### Schematic light drawing



### Ecodesign and Energy Labelling

   Replaceable (LED only) light source by an end-user

## Photometric

Lighting type	Direct
Light distribution	Symmetric
Extreme cut off	No

## Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Remote included
Dimmable	Yes
Power supply type	Dimmer on board
Dimming interface	Switch Integrated (Remote Dimmable)
Emergency	No

## Notes

Bulb not included. LED: max 8W - E14

---

## Bulbs



NOT INCLUDED

RF32290

LED Lamp E14 8W 2700K T28



NOT INCLUDED

RF32291

LED Lamp E14 8W 3000K T28