

FLOS

N35D144U30BDA White

In-Finity 35 Suspension Down 4000K Micro-Prismatic Diffuser Dali

Designed by FLOS Architectural, 2017



LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	28
Lumen Output (lm)	1384

Physical

Colour	White
Trim	No
Orientation	Fixed
Length (mm)	1405
Net weight (kg)	3.19
IP internal	20
IP external	20

Download

[Mounting instructions](#)  ZIP

Photometric Files

[LDT / IES](#)  ZIP


Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



Schematic light drawing



Beam Angle:	75°	
h(m)	E(lx)	D(m)
1	896	1.25
2	224	2.50
3	100	3.76
4	56	5.01
5	36	6.26

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	76
Beam angle C90-270 (°)	64

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable DALI 1
Emergency	No

Notes

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

Accessories & Power Supply



REQUIRED
Accessory

08.0030

Suspension kit



REQUIRED
Accessory

08.0031.00.DA

Power supply rose. Dali



REQUIRED
Accessory

08.9050.02

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey)

5



REQUIRED
Accessory

08.9050.40

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White)

5



REQUIRED
Accessory

08.9050.NS

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black)

5



OPTIONAL
Accessory

08.0112.00

500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam