

FLOS

N35DEM4G30B White

In-Finity 35 Suspension Down Emergency 4000K General Lighting

Designed by FLOS Architectural, 2018



LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	28
Lumen Output (lm)	1779

Physical

Colour	White
Trim	No
Orientation	Fixed
Length (mm)	1405
Net weight (kg)	3.19
IP internal	20
IP external	20

Download

[Mounting instructions](#)

[ZIP](#)



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	110
Beam angle C90-270 (°)	110

Electrical

Insulation class	I
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Emergency	Yes

Notes

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. /
Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

Accessories & Power Supply



REQUIRED
Accessory

08.0030

Suspension kit



REQUIRED
Accessory

08.0031.00

Power supply rose



REQUIRED
Accessory

08.9050.02

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey)

5



REQUIRED
Accessory

08.9050.40

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White)

5



REQUIRED
Accessory

08.9050.NS

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black)

5



OPTIONAL
Accessory

08.0109.00

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room