



In-Finity 70 Recessed Trim Emergency 4000K General Lighting Dali

Designed by FLOS Architectural



LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Wall recessed, Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Power (W)	32

Physical

Colour	Anodized Grey
Trim	No
Orientation	Fixed
Recessed depth (mm)	135
Length (mm)	1400
IP internal	40

Download

[Mounting instructions](#)



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	103
Beam angle C90-270 (°)	103

Electrical

Insulation class	I
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable DALI 1
Emergency	No

Notes

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. /
Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

Accessories & Power Supply



OPTIONAL
Accessory

08.0110.00

500 mm opal diffuser. Diffuse,
glare free and uniform lighting
throughout the room