



In-Finity 70 Suspension Down 4000K General Lighting

Designed by FLOS Architectural, 2017



LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Power (W)	26
Lumen Output (lm)	2733

Physical

Colour	Anodized Grey
Trim	No
Orientation	Fixed
Length (mm)	1125
Net weight (kg)	5
IP internal	20
IP external	20

Download

Mounting instructions [Download ZIP](#)

Photometric Files

LDT / IES [Download ZIP](#)


Technical Drawings

2D [Download ZIP](#)

3D [Download ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	102
Beam angle C90-270 (°)	106

Electrical

Insulation class	I
Frequency (Hz)	50/60
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Emergency	No

Notes

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. /
Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

Accessories & Power Supply



REQUIRED
Accessory

08.0030

Suspension kit



REQUIRED
Accessory

08.0031.00

Power supply rose



OPTIONAL
Accessory

08.0110.00

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room