

FLOS

F018C35AU13 Pale Green

In Vitro Ceiling

Designed by Philippe Starck, 2020



855lm - 3000K - CRI> 80 - Beam° 111

Ceiling-mounted outdoor lamp emitting diffused light. Opalescent diffuser integrated in the head with external transparent borosilicate safety glass. Structure in extruded and die-cast aluminium treated with chemical conversion process and powder-coated finish. Integrated LED light source with Edge Lighting technology. Integrated 220–240V ON/OFF, 1–10 V or DALI dimmable power supply.

Designed by Philippe Starck, In Vitro is an elegant outdoor lighting collection inspired by the idea of a contemporary lantern. An elegant, minimal frame creates the illusion of an empty glass volume, illuminated from within like a pure architectural form of light. Mounted overhead, In Vitro Ceiling produces a calm, enveloping glow that defines outdoor space with understated presence. The design captures Starck's signature balance of minimalism and innovation, resulting in a poetic yet highly functional light for outdoor environments.

Download

Mounting instructions



ZIP

Photometric Files

LDT / IES



ZIP

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



REPLACEABLE2



PWRSUPRPL2

Main specifications


EAN	8054793315430
Mounting	Ceiling
Environments	Outdoor wet location
Light Source Type	LED
Light sources included	Yes
LED type	Edge Lighting
Number of lamps	1
System power (W)	13
System flux (lm)	855

Physical


Color	Pale Green
Orientation	Fixed
Net weight (lb)	9.58
Gross weight (lb)	10.64
Package height (in)	9.25
Package width (in)	25.79
Package length (in)	15.16
Package volume (in)	3616.34
IP internal	66

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Schematic light drawing



Photometric

Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	111
Beam angle C90-270 (°)	111
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	110-277
Driver	Integrated
Emergency type	No

Notes

We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges

These effects are frequently caused by:

- over voltage coming from the mains' network where fixture is connected.
- electrostatic discharge (ESD) coming from the environment.

The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.
