

In Vitro Suspension Dimmable 1-10V

Designed by Philippe Starck, 2020

855lm - 3000K - CRI> 80 - Beam° 111



Outdoor suspension lamp emitting diffused light. Opalescent diffuser integrated in the head with external transparent borosilicate safety glass. Structure in extruded and die-cast aluminium treated with chemical conversion process and powder-coated finish. Integrated LED light source with Edge Lighting technology. Integrated 220–240V ON/OFF, 1–10 V or DALI dimmable power supply housed in the ceiling attachment. Suspension cable length 1000 mm.

Designed by Philippe Starck, In Vitro is an elegant outdoor lighting collection inspired by the idea of a contemporary lantern. An elegant, minimal frame creates the illusion of an empty glass volume, illuminated from within like a pure architectural form of light. Suspended in space, In Vitro Suspension reads as a floating volume of light, calm and atmospheric. The design captures Starck's signature balance of minimalism and innovation, resulting in a poetic yet highly functional light for outdoor environments.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8054793317472
Mounting	Suspension
Environments	Outdoor wet location
Light Source Type	LED
Light sources included	Yes
LED type	Edge Lighting
Number of lamps	1
System power (W)	13
System flux (lm)	855

Physical

Color	Deep Brown
Orientation	Fixed
Cord color	Black
Net weight (lb)	10.06
Gross weight (lb)	11.18
Package height (in)	9.25
Package width (in)	25.79
Package length (in)	15.16
Package volume (in)	3616.34
IP internal	66

Download

Mounting instructions [↓ ZIP](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F




REPLACEABLE2



PWRSUPRPL2



Schematic light drawing



Photometric

Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	111
Beam angle C90-270 (°)	111
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	110-240
Driver	Integrated
Dimmable	Yes
Dimming range (%)	1-100
Dimming interface	Dimmer Integrated
Emergency type	No

Notes

We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges

These effects are frequently caused by:

- over voltage coming from the mains' network where fixture is connected.
- electrostatic discharge (ESD) coming from the environment.

The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.
