

FLOS

F017H3LD006 Grey

Ingraze Adjustable Frame + Linear Louvre L 1200

Designed by FLOS Outdoor, 2023




1821lm - 3000K - CRI> 80 - Beam° 13

High-power LED source included and rear lenses. 1-10V or DALI on-off and dimmable 220-240V power supply. Compulsory installation box to be ordered separately. Pre-wired with H2O Stop quick connectors, lug/socket included. ACT (Anti-Corrosion Treatment) upon request.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

EAN	8054793286068
Mounting	In-ground
Environments	Outdoor wet location
LED type	Power LED
System power (W)	33.5
Lumen Output (lm)	1821

Physical

Colour	Grey
Orientation	Adjustable
Length (mm)	1200
Net weight (kg)	7.35
Package height (mm)	235
Package width (mm)	180
Package length (mm)	1272
Package volume (m3)	0.05
IP internal	66
IP external	67
Static load (kg)	2500.000
Drive Over	Yes

Download

Mounting instructions [ZIP](#)



Photometric Files

LDT / IES [ZIP](#)



Technical Drawings


2D [ZIP](#)



3D [ZIP](#)



Ecodesign and Energy Labelling




Replaceable (LED only) light source by a professional



Replaceable control gear by a professional



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	13
Beam angle C90-270 (°)	40

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Power supply type	Dimmable DALI 2

Accessories & Power Supply



REQUIRED Frame

Installation

F017Z040000

Framed installation box for single flush installations L 1200



REQUIRED Accessory

Electrical

F990C082000

5-pin connector kit with detachable socket + EU plug.



REQUIRED Frame

Installation

F017Z140000

Framed/frameless installation box for single installations L 1200



REQUIRED Accessory

Electrical

F990C083000

4-pin connector kit with detachable socket + EU plug.



OPTIONAL Accessory

F990C030000

4 way junction box 5 poles IP68 (6-14 mm cables)

OPTIONAL Accessory

F990C00A000

2 way terminal block 4 poles IP68 H20 stop. (ø5,5÷12mm cable)

OPTIONAL Accessory

F990C010000

3/4 way terminal block 4 poles IP68 H20 stop. (ø5,5÷12mm cable)

OPTIONAL Accessory

F990C080000

Connector kit 5-pole flying socket + EU plug IP68.



OPTIONAL
Frame
Installation

F017Z550006

Framed anti-theft bracket kit.



OPTIONAL
Frame
Installation

F017Z240000

Framed flush continuous line
module L 1200



OPTIONAL
Frame
Installation

F017Z640000

Complete framed anti-theft
installation box for single flush
installations L 1200



OPTIONAL
Frame
Installation

F017Z740000

Framed/frameless anti-theft
installation box for single
installations L 1200



OPTIONAL
Frame
Installation

F017Z241000

Framed/frameless continuous
line module L 1200



OPTIONAL
Frame
Installation

F017Z490000

Standard end-plate cover kit.



OPTIONAL
Frame
Installation

F017Z560033

Frameless anti-theft bracket kit.



OPTIONAL
Accessory
Electrical

F990C081000

4-pin connector kit with
detachable socket + IP68 EU plug.



OPTIONAL
Frame

Installation

F017Z550033

Framed anti-theft bracket kit.



OPTIONAL
Frame

Installation

F017Z530000

Standard connecting plate kit.



OPTIONAL
Frame

Installation

F017Z531000

Anti-theft connecting plate kit.



OPTIONAL
Frame

Installation

F017Z560006

Frameless anti-theft bracket kit.