

FLOS

F017Q4JB006 Grey

Ingraze Adjustable Frameless + Linear Louvre L 900

Designed by FLOS Outdoor, 2023




1830lm - 4000K - CRI> 80 - Beam° 25

High-power LED source included and rear lenses. 1-10V or DALI on-off and dimmable 220-240V power supply. Compulsory installation box to be ordered separately. Pre-wired with H2O Stop quick connectors, lug/socket included. ACT (Anti-Corrosion Treatment) upon request.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793307220
Mounting	In-ground
LED type	Power LED
System power (W)	26
Lumen Output (lm)	1830

Physical

Colour	Grey
Orientation	Adjustable
Length (mm)	900
Net weight (kg)	6.25
Package height (mm)	230
Package width (mm)	170
Package length (mm)	972
Package volume (m3)	0.04
IP internal	66
IP external	67
Static load (kg)	2500.000
Drive Over	Yes

Download

Mounting instructions  ZIP

Photometric Files

LDT / IES  ZIP

Technical Drawings


2D  ZIP

3D  ZIP

Ecodesign and Energy Labelling




Replaceable (LED only)
light source by a
professional



Replaceable control
gear by a professional



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	25
Beam angle C90-270 (°)	22

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Power supply type	Dimmable 1-10V

Accessories & Power Supply

			
REQUIRED Accessory	REQUIRED Accessory	REQUIRED Frame	OPTIONAL Accessory
Electrical	Electrical	Installation	
F990C082000 5-pin connector kit with detachable socket + EU plug.	F990C083000 4-pin connector kit with detachable socket + EU plug.	F017Z130000 Framed/frameless installation box for single installations L 900	F990C080000 Connector kit 5-pole flying socket + EU plug IP68.
			
OPTIONAL Accessory	OPTIONAL Accessory	OPTIONAL Accessory	OPTIONAL Accessory
F990C030000 4 way junction box 5 poles IP68 (6-14 mm cables)	F990C00A000 2 way terminal block 4 poles IP68 H20 stop. (ø5,5÷12mm cable)	F990C010000 3/4 way terminal block 4 poles IP68 H2O stop. (ø5,5÷12mm cable)	Electrical F990C081000 4-pin connector kit with detachable socket + IP68 EU plug.



OPTIONAL
Frame

Installation

F017Z231000

Framed/frameless continuous
line module L 900



OPTIONAL
Frame

Installation

F017Z490000

Standard end-plate cover kit.



OPTIONAL
Frame

Installation

F017Z530000

Standard connecting plate kit.



OPTIONAL
Frame

Installation

F017Z531000

Anti-theft connecting plate kit.



OPTIONAL
Frame

Installation

F017Z550006

Framed anti-theft bracket kit.



OPTIONAL
Frame

Installation

F017Z550033

Framed anti-theft bracket kit.



OPTIONAL
Frame

Installation

F017Z730000

Framed/frameless anti-theft
installation box for single
installations L 900