

Ingraze Fixed Frame + Asymmetric Louvre L 1200

Designed by FLOS Outdoor, 2023



859lm - 3000K - CRI> 80 - Beam° 12

High-power LED source included and rear lenses. 1-10V or DALI on-off and dimmable 220-240V power supply. Compulsory installation box to be ordered separately. Pre-wired with H2O Stop quick connectors, lug/socket included. ACT (Anti-Corrosion Treatment) upon request.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8054793274539
Mounting	In-ground
LED type	Power LED
System power (W)	33.5
Lumen Output (lm)	859

Physical

Colour	Anthracite
Orientation	Fixed
Length (mm)	1200
Net weight (kg)	6.76
Package height (mm)	235
Package width (mm)	180
Package length (mm)	1272
Package volume (m3)	0.05
IP internal	66
IP external	67
Static load (kg)	2500.000
Dynamic load (kg)	Yes

Download

Mounting instructions	ZIP
Mounting instructions	ZIP
Mounting instructions	ZIP
Mounting instructions	ZIP

Photometric Files

LDT / IES	ZIP
LDT / IES	ZIP
LDT / IES	ZIP

Technical Drawings

2D	ZIP
2D	ZIP
2D	ZIP
2D	ZIP
3D	ZIP
3D	ZIP
3D	ZIP
3D	ZIP



Ecodesign and Energy Labelling




REPLACEABLE2



PWRSUPRPL2

Schematic light drawing




Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	12
Beam angle C90-270 (°)	40

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Power supply type	Dimmable DALI 2

Accessories & Power Supply



REQUIRED
Frame

ACCESSORYTYPE2

F017Z040000

Framed installation box for single flush installations L 1200



REQUIRED
Frame

ACCESSORYTYPE2

F017Z140000

Framed/frameless installation box for single installations L 1200



REQUIRED
Accessory

ACCESSORYTYPE1

F990C082000

5-pin connector kit with detachable socket + EU plug.



REQUIRED
Accessory

ACCESSORYTYPE1

F990C083000

4-pin connector kit with detachable socket + EU plug.



OPTIONAL
Frame

ACCESSORYTYPE2

F017Z240000

Framed flush continuous line module L 1200



OPTIONAL
Frame

ACCESSORYTYPE2

F017Z241000

Framed/frameless continuous line module L 1200



OPTIONAL
Frame

ACCESSORYTYPE2

F017Z490000

Standard end-plate cover kit.



OPTIONAL
Frame

ACCESSORYTYPE2

F017Z530000

Standard connecting plate kit.



OPTIONAL
Frame

ACCESSORYTYPE2

F017Z531000

Anti-theft connecting plate kit.



OPTIONAL
Frame

ACCESSORYTYPE2

F017Z550006

Framed anti-theft bracket kit.



OPTIONAL
Frame

ACCESSORYTYPE2

F017Z550033

Framed anti-theft bracket kit.



OPTIONAL
Frame

ACCESSORYTYPE2

F017Z560006

Frameless anti-theft bracket kit.



OPTIONAL
Frame

ACCESSORYTYPE2

F017Z560033

Frameless anti-theft bracket kit.



OPTIONAL
Frame

ACCESSORYTYPE2

F017Z640000

Complete framed anti-theft
installation box for single flush
installations L 1200



OPTIONAL
Frame

ACCESSORYTYPE2

F017Z740000

Framed/frameless anti-theft
installation box for single
installations L 1200



OPTIONAL
Accessory

F990C00A000

2 way terminal block 4 poles IP68
H20 stop. (ø5,5÷12mm cable)



OPTIONAL
Accessory

F990C010000

3/4 way terminal block 4 poles
IP68 H2O stop. (ø5,5÷12mm
cable)



OPTIONAL
Accessory

F990C030000

4 way junction box 5 poles IP68
(6-14 mm cables)



OPTIONAL
Accessory

F990C080000

Connector kit 5-pole flying socket
+ EU plug IP68.



OPTIONAL
Accessory

ACCESSORYTYPE1

F990C081000

4-pin connector kit with
detachable socket + IP68 EU plug.