

FLOS

 F017D2AB033 Anthracite

Ingraze Fixed Frame L 1200

Designed by FLOS Outdoor, 2023




2837lm - 2700K - CRI> 80 - Beam° 16

High-power LED source included and rear lenses. 1-10V or DALI on-off and dimmable 220-240V power supply. Compulsory installation box to be ordered separately. Pre-wired with H2O Stop quick connectors, lug/socket included. ACT (Anti-Corrosion Treatment) upon request.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

EAN	8054793273099
Mounting	In-ground
LED type	Power LED
System power (W)	33.5
Lumen Output (lm)	2837

Physical

Colour	Anthracite
Orientation	Fixed
Length (mm)	1200
Net weight (kg)	6.76
Package height (mm)	235
Package width (mm)	180
Package length (mm)	1272
Package volume (m3)	0.05
IP internal	66
IP external	67
Static load (kg)	2500.000
Drive Over	Yes

Download

Mounting instructions [ZIP](#)

Photometric Files

LDT / IES [ZIP](#)

Technical Drawings

2D [ZIP](#)

3D [ZIP](#)




Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional

 Replaceable control gear by a professional

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	16
Beam angle C90-270 (°)	16

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Power supply type	Dimmable 1-10V

Accessories & Power Supply



REQUIRED
Accessory

Electrical


F990C083000
4-pin connector kit with detachable socket + EU plug.



REQUIRED
Accessory

Electrical

F990C082000
5-pin connector kit with detachable socket + EU plug.



REQUIRED
Frame

Installation

F017Z040000
Framed installation box for single flush installations L 1200



REQUIRED
Frame

Installation

F017Z140000
Framed/frameless installation box for single installations L 1200



OPTIONAL
Accessory

F990C00A000
2 way terminal block 4 poles IP68 H2O stop. (ø5,5÷12mm cable)



OPTIONAL
Accessory

F990C030000
4 way junction box 5 poles IP68 (6-14 mm cables)



OPTIONAL
Accessory

F990C010000
3/4 way terminal block 4 poles IP68 H2O stop. (ø5,5÷12mm cable)



OPTIONAL
Accessory

F990C080000
Connector kit 5-pole flying socket + EU plug IP68.



OPTIONAL
Accessory

Electrical

F990C081000

4-pin connector kit with detachable socket + IP68 EU plug.



OPTIONAL
Frame

Installation

F017Z240000

Framed flush continuous line module L 1200



OPTIONAL
Frame

Installation

F017Z241000

Framed/frameless continuous line module L 1200



OPTIONAL
Frame

Installation

F017Z490000

Standard end-plate cover kit.



OPTIONAL
Frame

Installation

F017Z530000

Standard connecting plate kit.



OPTIONAL
Frame

Installation

F017Z531000

Anti-theft connecting plate kit.



OPTIONAL
Frame

Installation

F017Z550006

Framed anti-theft bracket kit.



OPTIONAL
Frame

Installation

F017Z550033

Framed anti-theft bracket kit.



OPTIONAL
Frame

Installation

F017Z560006

Frameless anti-theft bracket kit.



OPTIONAL
Frame

Installation

F017Z560033

Frameless anti-theft bracket kit.



OPTIONAL
Frame

Installation

F017Z640000

Complete framed anti-theft
installation box for single flush
installations L 1200



OPTIONAL
Frame

Installation

F017Z740000

Framed/frameless anti-theft
installation box for single
installations L 1200