

FLOS

F017A1HA006 Grey

Ingraze Fixed Frame + Linear Louvre L 400

Designed by FLOS Outdoor, 2023




702lm - 2200K - CRI>80 - Beam° 16

High-power LED source included and rear lenses. 1-10V or DALI on-off and dimmable 220-240V power supply. Compulsory installation box to be ordered separately. Pre-wired with H2O Stop quick connectors, lug/socket included. ACT (Anti-Corrosion Treatment) upon request.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

EAN	8054793259765
Mounting	In-ground
Environments	Outdoor wet location
LED type	Power LED
System power (W)	12.5
Lumen Output (lm)	702

Physical

Colour	Grey
Orientation	Fixed
Length (mm)	400
Net weight (kg)	2.45
Package height (mm)	220
Package width (mm)	170
Package length (mm)	472
Package volume (m3)	0.02
IP internal	66
IP external	67
Static load (kg)	2500.000

Download

Mounting instructions [ZIP](#)



Photometric Files

LDT / IES [ZIP](#)



Technical Drawings


2D [ZIP](#)



3D [ZIP](#)



Ecodesign and Energy Labelling




Replaceable (LED only) light source by a professional



Replaceable control gear by a professional



Schematic light drawing



Beam Angle: 16°		
h(m)	E(lx)	D(m)
1	5699	0.28
2	1425	0.56
3	633	0.83
4	356	1.11
5	228	1.39

Luminous flux luminaire
702 lm

Photometric

Light distribution	Symmetric
CCT (K)	2200
CRI>	80
Beam angle C0-180 (°)	16
Beam angle C90-270 (°)	16

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Power supply type	Non Dimmable

Accessories & Power Supply



REQUIRED Accessory

Electrical

F990C082000

5-pin connector kit with
detachable socket + EU plug.



REQUIRED Accessory

Electrical

F990C083000

4-pin connector kit with
detachable socket + EU plug.



REQUIRED Frame

Installation

F017Z010000

Framed installation box for single
flush installations.



REQUIRED Frame

Installation

F017Z110000

Framed/frameless installation box
for single installations.



OPTIONAL Accessory

F990C080000

Connector kit 5-pole flying socket
+ EU plug IP68.

OPTIONAL Accessory

F990C030000

4 way junction box 5 poles IP68
(6-14 mm cables)

OPTIONAL Accessory

F990C00A000

2 way terminal block 4 poles IP68
H20 stop. (ø5,5÷12mm cable)

OPTIONAL Accessory

F990C010000

3/4 way terminal block 4 poles
IP68 H20 stop. (ø5,5÷12mm
cable)



OPTIONAL
Frame
Installation

F017Z210000

Framed flush continuous line module.



OPTIONAL
Frame
Installation

F017Z710000

Framed/frameless anti-theft installation box for single installations.



OPTIONAL
Frame
Installation

F017Z560006

Frameless anti-theft bracket kit.



OPTIONAL
Frame
Installation

F017Z211000

Framed/frameless continuous line module.



OPTIONAL
Frame
Installation

F017Z610000

Complete framed anti-theft installation box for single flush installations.



OPTIONAL
Accessory
Electrical

F990C081000

4-pin connector kit with detachable socket + IP68 EU plug.



OPTIONAL
Frame
Installation

F017Z490000

Standard end-plate cover kit.



OPTIONAL
Frame
Installation

F017Z530000

Standard connecting plate kit.



OPTIONAL
Frame

Installation

F017Z550033

Framed anti-theft bracket kit.



OPTIONAL
Frame

Installation

F017Z531000

Anti-theft connecting plate kit.



OPTIONAL
Frame

Installation

F017Z550006

Framed anti-theft bracket kit.



OPTIONAL
Frame

Installation

F017Z560033

Frameless anti-theft bracket kit.