

Ingraze Fixed Frame + Linear Louvre L 600

Designed by FLOS Outdoor, 2023




852lm - 2700K - CRI> 80 - Beam° 39

High-power LED source included and rear lenses. 1-10V or DALI on-off and dimmable 220-240V power supply. Compulsory installation box to be ordered separately. Pre-wired with H2O Stop quick connectors, lug/socket included. ACT (Anti-Corrosion Treatment) upon request.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

EAN	8054793267593
Mounting	In-ground
LED type	Power LED
System power (W)	17
Lumen Output (lm)	852

Physical

Colour	Grey
Orientation	Fixed
Length (mm)	600
Net weight (kg)	3.55
Package height (mm)	225
Package width (mm)	170
Package length (mm)	672
Package volume (m3)	0.03
IP internal	66
IP external	67
Static load (kg)	2500.000
Drive Over	Yes

Download

Mounting instructions [↓ ZIP](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)


3D [↓ ZIP](#)



Ecodesign and Energy Labelling



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	39
Beam angle C90-270 (°)	44

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Power supply type	Dimmable DALI 2

Accessories & Power Supply



REQUIRED
Accessory

Electrical


F990C082000
5-pin connector kit with detachable socket + EU plug.



REQUIRED
Accessory

Electrical

F990C083000
4-pin connector kit with detachable socket + EU plug.



REQUIRED
Frame

Installation

F017Z020000
Framed installation box for single flush installations L600



REQUIRED
Frame

Installation

F017Z120000
Framed/frameless installation box for single installations L600



OPTIONAL
Accessory

F990C030000
4 way junction box 5 poles IP68 (6-14 mm cables)



OPTIONAL
Accessory

F990C00A000
2 way terminal block 4 poles IP68 H20 stop. (ø5,5÷12mm cable)



OPTIONAL
Accessory

F990C010000
3/4 way terminal block 4 poles IP68 H2O stop. (ø5,5÷12mm cable)



OPTIONAL
Accessory

F990C080000
Connector kit 5-pole flying socket + EU plug IP68.



OPTIONAL
Accessory

Electrical

F990C081000

4-pin connector kit with detachable socket + IP68 EU plug.



OPTIONAL
Frame

Installation

F017Z220000

Framed flush continuous line module 600L



OPTIONAL
Frame

Installation

F017Z221000

Framed/frameless continuous line module L600



OPTIONAL
Frame

Installation

F017Z490000

Standard end-plate cover kit.



OPTIONAL
Frame

Installation

F017Z530000

Standard connecting plate kit.



OPTIONAL
Frame

Installation

F017Z531000

Anti-theft connecting plate kit.



OPTIONAL
Frame

Installation

F017Z550006

Framed anti-theft bracket kit.



OPTIONAL
Frame

Installation

F017Z550033

Framed anti-theft bracket kit.



OPTIONAL
Frame

Installation

F017Z560006

Frameless anti-theft bracket kit.



OPTIONAL
Frame

Installation

F017Z560033

Frameless anti-theft bracket kit.



OPTIONAL
Frame

Installation

F017Z620000

Complete framed anti-theft
installation box for single flush
installations 600L



OPTIONAL
Frame

Installation

F017Z720000

Framed/frameless anti-theft
installation box for single
installations 600L