

Ingraze Fixed Frameless + Asymmetric Louvre L 600

Designed by FLOS Outdoor, 2023




419lm - 2700K - CRI> 80 - Beam° 42

High-power LED source included and rear lenses. 1-10V or DALI on-off and dimmable 220-240V power supply. Compulsory installation box to be ordered separately. Pre-wired with H2O Stop quick connectors, lug/socket included. ACT (Anti-Corrosion Treatment) upon request.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

EAN	8054793291338
Mounting	In-ground
LED type	Power LED
System power (W)	17
Lumen Output (lm)	419

Physical

Colour	Anthracite
Orientation	Fixed
Length (mm)	600
Net weight (kg)	3.99
Package height (mm)	225
Package width (mm)	170
Package length (mm)	672
Package volume (m3)	0.03
IP internal	66
IP external	67
Static load (kg)	2500.000
Drive Over	Yes

Download

[Mounting instructions](#)  ZIP

Photometric Files


[LDT / IES](#)  ZIP

Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP


Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional

 Replaceable control gear by a professional



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	42
Beam angle C90-270 (°)	44

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Power supply type	Dimmable DALI 2

Accessories & Power Supply

			
REQUIRED Accessory	REQUIRED Accessory	REQUIRED Frame	OPTIONAL Accessory
Electrical	Electrical	Installation	
F990C083000 4-pin connector kit with detachable socket + EU plug.	F990C082000 5-pin connector kit with detachable socket + EU plug.	F017Z120000 Framed/frameless installation box for single installations L600	F990C080000 Connector kit 5-pole flying socket + EU plug IP68.
			
OPTIONAL Accessory	OPTIONAL Accessory	OPTIONAL Accessory	OPTIONAL Accessory
F990C00A000 2 way terminal block 4 poles IP68 H2O stop. (ø5,5÷12mm cable)	F990C030000 4 way junction box 5 poles IP68 (6-14 mm cables)	F990C010000 3/4 way terminal block 4 poles IP68 H2O stop. (ø5,5÷12mm cable)	Electrical F990C081000 4-pin connector kit with detachable socket + IP68 EU plug.



OPTIONAL
Frame

Installation

F017Z221000

Framed/frameless continuous
line module L600



OPTIONAL
Frame

Installation

F017Z490000

Standard end-plate cover kit.



OPTIONAL
Frame

Installation

F017Z530000

Standard connecting plate kit.



OPTIONAL
Frame

Installation

F017Z531000

Anti-theft connecting plate kit.



OPTIONAL
Frame

Installation

F017Z550006

Framed anti-theft bracket kit.



OPTIONAL
Frame

Installation

F017Z550033

Framed anti-theft bracket kit.



OPTIONAL
Frame

Installation

F017Z720000

Framed/frameless anti-theft
installation box for single
installations 600L