FLOS

F017L4AD006 Grey

Ingraze Fixed Frameless L 900

Designed by FLOS Outdoor, 2023

2356lm - 4000K - CRI> 80 - Beam° 16

High-power LED source included and rear lenses. 1-10V or DALI on-off and dimmable 220-240V power supply. Compulsory installation box to be ordered separately. Pre-wired with H2O Stop quick connectors, lug/socket included. ACT (Anti-Corrosion Treatment) upon request.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

EAN	8054793295169
Mounting	In-ground
LED type	Power LED
System power (W)	26
Lumen Output (lm)	2356

Physical

Colour	Grey
Orientation	Fixed
Length (mm)	900
Net weight (kg)	5.79
Package height (mm)	230
Package width (mm)	170
Package length (mm)	972
Package volume (m3)	0.04
IP internal	66
IP external	67
Static load (kg)	2500.000
Drive Over	Yes

Download

Mounting instructions ZIP

Photometric Files

LDT / IES ZIP

Technical Drawings

2D ZIP

3D ZIP

Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

RG IEC 62471 | IP 67 | IK 10

©2026 Flos - P.IVA 00290820174 - 5/31/2026

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Schematic light drawing



Luminous flux luminaire
2536 lm

Beam Angle: 16°

h(m)	E(lx)	D(m)
1	17648	0.27
2	4412	0.55
3	1961	0.82
4	1103	1.09
5	706	1.37

Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	16
Beam angle C90-270 (°)	16

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Power supply type	Dimmable DALI 2

©2026 Flos - P.IVA 00290820174 - 5/31/2026

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Accessories & Power Supply

REQUIRED
Accessory

Electrical

F990C083000

4-pin connector kit with detachable socket + EU plug.

REQUIRED
Accessory

Electrical

F990C082000

5-pin connector kit with detachable socket + EU plug.

REQUIRED
Frame

Installation

F017Z130000

Framed/frameless installation box for single installations L 900

OPTIONAL
Accessory

F990C030000

4 way junction box 5 poles IP68 (6-14 mm cables)

OPTIONAL
Accessory

F990C00A000

2 way terminal block 4 poles IP68 H20 stop. (ø5,5÷12mm cable)

OPTIONAL
Accessory

F990C010000

3/4 way terminal block 4 poles IP68 H2O stop. (ø5,5÷12mm cable)

OPTIONAL
Accessory

F990C080000

Connector kit 5-pole flying socket + EU plug IP68.

OPTIONAL
Accessory

Electrical

F990C081000

4-pin connector kit with detachable socket + IP68 EU plug.

©2026 Flos - P.IVA 00290820174 - 5/31/2026

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

OPTIONAL
Frame

Installation

F017Z231000

Framed/frameless continuous line module L 900

OPTIONAL
Frame

Installation

F017Z490000

Standard end-plate cover kit.

OPTIONAL
Frame

Installation

F017Z530000

Standard connecting plate kit.

OPTIONAL
Frame

Installation

F017Z531000

Anti-theft connecting plate kit.

OPTIONAL
Frame

Installation

F017Z550006

Framed anti-theft bracket kit.

OPTIONAL
Frame

Installation

F017Z550033

Framed anti-theft bracket kit.

OPTIONAL
Frame

Installation

F017Z730000

Framed/frameless anti-theft installation box for single installations L 900

©2026 Flos - P.IVA 00290820174 - 5/31/2026

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.