

Johnny 80 Trim 2L Square ELV - 120V

Designed by FLOS Architectural



Recessed luminaire with LED light source. Power supply not included. Requires one power supply for each optic body.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	2
Power (W)	6.2
System flux (lm)	311

Physical

Color	Black
Trim	Yes
Orientation	Adjustable
Longitudinal tilting (°)	20
Transversal tilting (°)	20
Net weight (lb)	0.99
Package volume (in)	916
IP internal	20



Download

Family spec sheetZIP


Mounting instructionsPDF

Photometric Files

LDT / IESZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	31
Beam angle C90-270 (°)	31

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	120
LED current (mA)	500
Driver	Remote included
Dimmable	Yes
Dimming type	Mains Cut Dimming

Notes

Accessories included (honeycomb and screening crosspiece).



OPTIONAL
Housing and Hanger Bar

TRAY-0003

Registration Tray - non electrical,
place holder for non IC new
construction, Johnny 80 2 Lights
Trim, 2.95 x 5.79"