

Kap Ø 105 Fixed

Designed by FLOS Architectural, 2019

LED retrofit



Recessed 12V lamp luminaire. Remote transformer not included.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	Bulb
Light sources included	no
Lamp category	LED retrofit
Lamp type	QR-CBC 51
Lamp holders	GX5.3

Physical

Colour	Gold
Trim	No
Orientation	Fixed
Recessed depth (mm)	130
Spot diameter (mm)	105
Length (mm)	105
Net weight (kg)	0.23
Package height (mm)	190
Package width (mm)	175
Package length (mm)	220
IP internal	54




Download


Mounting instructions

PDF

Ecodesign and Energy Labelling



Replaceable (LED only) light source by an end-user



Replaceable control gear by a professional



Photometric

Lighting type	Direct
Light distribution	Symmetric

Electrical


Insulation class	II
Forward voltage (V)	12
Power supply	Remote excluded

Notes

Not suitable for lens accessories. Check your lamp dimentions to match the product.



Accessories & Power Supply



ø120



REQUIRED
Frame

ACCESSORYTYPE2

08.0132.00

Installation frame No Trim