

Kap Ø 105 Wall-Washer

Designed by FLOS Architectural, 2019

LED retrofit

Recessed 12V LED lamp luminaire. Remote transformer not included.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	Bulb
Light sources included	no
Lamp category	LED retrofit
Lamp type	QR-CBC 51
Lamp holders	GX5.3

Physical

Colour	Black
Trim	No
Orientation	Fixed
Recessed depth (mm)	130
Spot diameter (mm)	105
Length (mm)	105
Net weight (kg)	0.21
Package height (mm)	190
Package width (mm)	175
Package length (mm)	220
IP internal	54



Download

Mounting instructions  PDF

Photometric Files


LDT / IES  ZIP

Technical Drawings

 Bim  ZIP



Ecodesign and Energy Labelling



Photometric

Lighting type	Direct
Light distribution	Asymmetric


Electrical

Insulation class	II
Forward voltage (V)	12
Power supply	Remote excluded

Notes

Not suitable for lens accessories. Check your lamp dimentions to match the product.

Accessories & Power Supply



ø120



REQUIRED
Frame

ACCESSORYTYPE2

08.0132.00

Installation frame No Trim