

FLOS

05.7141.74 Black

Kap Ø 105 Wall-Washer

Designed by FLOS Architectural, 2019

LED

Recessed luminaire with main voltage source.



Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	Bulb
Light sources included	no
Lamp category	LED
Lamp type	PAR16
Lamp holders	GZ10
Number of lamps	1

Physical

Colour	Black
Trim	No
Orientation	Fixed
Recessed depth (mm)	155
Spot diameter (mm)	105
Length (mm)	105
Net weight (kg)	0.21
Package height (mm)	190
Package width (mm)	175
Package length (mm)	220
IP internal	54



Download

Mounting instructions [Download PDF](#)

Photometric Files

LDT / IES [Download ZIP](#)

Technical Drawings

2D [Download ZIP](#)

3D [Download ZIP](#)

[Bim](#) [Download ZIP](#)



Ecodesign and Energy Labelling




Photometric

Lighting type	Direct
Light distribution	Asymmetric

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Forward voltage (V)	230

Accessories & Power Supply



ø120



REQUIRED
Frame

ACCESSORYTYPE2

08.0132.00

Installation frame No Trim