

Kap Ø 80 Adjustable

Designed by FLOS Architectural, 2016



Recessed 12V lamp luminaire. Remote transformer not included.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	Bulb
Light sources included	no
Lamp category	LED retrofit
Lamp type	QR-CBC 51
Lamp holders	GX5.3
Number of lamps	1

Physical

Colour	Gold
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	20
Transversal tilting (°)	20
Recessed depth (mm)	120
Spot diameter (mm)	74
Length (mm)	74
Net weight (kg)	0.12
Package height (mm)	90
Package width (mm)	140
Package length (mm)	105
IP internal	20
IP external	23



Download

Mounting instructions

[PDF](#)

Ecodesign and Energy Labelling

Replaceable (LED only) light source by an end-user

Replaceable control gear by a professional



Photometric

Lighting type	Direct
Light distribution	Symmetric

Electrical

Insulation class	III
Forward voltage (V)	12
Power supply	Remote excluded

Notes

Not suitable for lens accessories. Check your lamp dimentions to match the product.



Accessories & Power Supply



REQUIRED
Frame

Installation

08.9102.00

Installation frame No Trim