

Kap Ø 80 Adjustable

Designed by FLOS Architectural, 2016

LED retrofit

Recessed luminaire with main voltage source.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	Bulb
Light sources included	no
Lamp category	LED retrofit
Lamp type	PAR16
Lamp holders	GZ10
Number of lamps	1

Physical

Colour	Gold
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	20
Transversal tilting (°)	20
Recessed depth (mm)	155
Spot diameter (mm)	74
Length (mm)	74
Net weight (kg)	0.12
Package height (mm)	90
Package width (mm)	140
Package length (mm)	105
IP internal	20
IP external	23



Download

Mounting instructions

PDF

Ecodesign and Energy Labelling



Replaceable (LED only)
light source by an end-user



Photometric

Lighting type	Direct
Light distribution	Symmetric

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Forward voltage (V)	230

Notes

Not suitable for lens accessories.



Accessories & Power Supply



REQUIRED
Frame

ACCESSORYTYPE2

08.9102.00

Installation frame No Trim