

## Kap Ø 80 Fixed Optic Medium - Non IC


Designed by FLOS Architectural, 2016

9.2W - 594lm - 2700K - CRI> 90 - Beam° 26

Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | LED array           |
| Number of lamps        | 1                   |
| Power (W)              | 9.2                 |
| Source flux (lm)       | 908                 |
| System flux (lm)       | 594                 |
| Efficacy (lm/W)        | 64                  |

### Physical

|                   |       |
|-------------------|-------|
| Color             | Gold  |
| Trim              | Yes   |
| Orientation       | Fixed |
| Net weight (lb)   | 7.77  |
| Gross weight (lb) | 9.15  |
| IP internal       | 20    |
| IP external       | 54    |

### Download


Family spec sheet [↓ ZIP](#)  
Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)



Schematic light drawing



Photometric

|                          |                             |
|--------------------------|-----------------------------|
| Lighting type            | Direct                      |
| Light distribution       | Symmetric                   |
| CCT (K)                  | 2700                        |
| CRI>                     | 90                          |
| McAdam steps (SDCM)      | 3                           |
| LED Life / Failure Ratio | L80B50>50.000h<br>(Tc=85°C= |
| Beam angle C0-180 (°)    | 26                          |
| Beam angle C90-270 (°)   | 26                          |

Electrical

|                     |      |
|---------------------|------|
| Insulation class    | III  |
| Forward voltage (V) | 18.4 |
| LED current (mA)    | 500  |

Notes

Diffusing lens included.

Accessories & Power Supply



REQUIRED  
Power supply

SP14W500MA-ELV-E01  
Splice Box 9"x2"x1.5", 500mA ,  
14W, ELV Dimmable, Thermal  
120V



REQUIRED  
Power supply

ACCESSORYTYPE1  
SP20W500MA-277-V01  
Splice Box 9" x 2" x 1.5", 500mA,  
20W, 0-10V, 277V



REQUIRED  
Power supply

ACCESSORYTYPE1  
SP14W500MA-120-V01  
Splice Box 14W, 1% dim, 0-10V,  
120V.



REQUIRED  
Frame

ACCESSORYTYPE2  
08.9102.00  
Installation frame No Trim



OPTIONAL  
Housing and Hanger Bar

TRAY-0016  
Registration Tray - non electrical,  
place holder for non IC new  
construction Round, Ø4'''