

Kap 80 Square Wall-Washer

Designed by FLOS Architectural, 2016



Recessed 12V lamp luminaire. Remote transformer not included.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	Bulb
Light sources included	no
Lamp category	LED retrofit
Lamp type	QR-CBC 51
Lamp holders	GX5.3
Number of lamps	1

Physical

Colour	White
Trim	No
Orientation	Fixed
Recessed depth (mm)	130
Length (mm)	74
Net weight (kg)	0.12
Package height (mm)	90
Package width (mm)	140
Package length (mm)	105
IP internal	20
IP external	23



Download

Mounting instructions	PDF
Item information	JPG

Photometric Files

LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP
Bim	ZIP



Photometric

Lighting type	Direct, Indirect
Light distribution	Asymmetric


Electrical

Insulation class	II
Forward voltage (V)	12
Power supply	Remote excluded


Notes

Not suitable for lens accessories. Check your lamp dimentions to match the product.

Ecodesign and Energy
Labelling




Replaceable (LED only)
light source by an end-
user



Replaceable control
gear by a professional

Accessories & Power Supply



REQUIRED
Frame

Installation

08.9103.00

Installation frame No Trim