

Kap Ø 80 Wall-Washer - Non IC


Designed by FLOS Architectural, 2016

9.2W - 590lm - 3000K - CRI> 90 - Beam° 30

Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
Power (W)	9.2
Source flux (lm)	956
System flux (lm)	590
Efficacy (lm/W)	67

Physical

Color	Gold
Trim	Yes
Orientation	Fixed
Net weight (lb)	7.77
Gross weight (lb)	9.15
IP internal	20
IP external	54

Download


- Family spec sheet [ZIP](#)
- Mounting instructions [PDF](#)

Photometric Files

- LDT / IES [ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct, Indirect
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C=
Beam angle C0-180 (°)	30
Beam angle C90-270 (°)	36

Electrical

Insulation class	III
Forward voltage (V)	18.4
LED current (mA)	500

Notes

Diffusing lens included.

Accessories & Power Supply



REQUIRED
Power supply

SP14W500MA-ELV-E01
Splice Box 9"x2"x1.5", 500mA ,
14W, ELV Dimmable, Thermal
120V



REQUIRED
Power supply

ACCESSORYTYPE1
SP20W500MA-277-V01
Splice Box 9" x 2" x 1.5", 500mA,
20W, 0-10V, 277V



REQUIRED
Power supply

ACCESSORYTYPE1
SP14W500MA-120-V01
Splice Box 14W, 1% dim, 0-10V,
120V.



REQUIRED
Frame

ACCESSORYTYPE2
08.9102.00
Installation frame No Trim



OPTIONAL
Housing and Hanger Bar

TRAY-0016
Registration Tray - non electrical,
place holder for non IC new
construction Round, Ø4'''