

FLOS

03.5810.ASB Brushed Aluminium/White

Kap Suspension Ø 100

Designed by FLOS Architectural, 2020

LED - Power LED - 9W - 550lm - 3000K - CRI> 80 - Beam° 29



Hanging luminaire for mounting in ceiling with led light source. non-regulable
110/240V, 50/60hz power supply integrated in luminaire body.

Are you a professional and your project needs
consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	9
System power (W)	11
Source flux (lm)	1000
Lumen Output (lm)	550

Physical

Colour	Brushed Aluminium/White
Spot diameter (mm)	100
Length (mm)	100
Net weight (kg)	2.27
Package height (mm)	220
Package width (mm)	380
Package length (mm)	150
IP internal	20



Download

Mounting instructions [Download PDF](#)

Item information [Download JPG](#)

Photometric Files

LDT / IES [Download ZIP](#)

Technical Drawings


2D [Download ZIP](#)

3D [Download ZIP](#)

[Bim](#) [Download ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	80
McAdam steps (SDCM)	3
Beam angle C0-180 (°)	29
Beam angle C90-270 (°)	29

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	110-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable