

# FLOS

F002B20AU01.A White

## Klein Pro H 900 mm Dimmable White


Designed by FLOS Outdoor, 2017



Solid surface or ground installation accessories to be ordered separately. Each luminaire is equipped with 1000 mm length outgoing cable and a wiring kit.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

EAN	8054793181431
Mounting	Ground
Environments	Outdoor wet location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	11
System power (W)	11
System flux (lm)	99

### Physical

Color	White
Orientation	Fixed
Net weight (lb)	4.76
Gross weight (lb)	5.29
Package height (in)	4.61
Package width (in)	39.76
Package length (in)	4.53
Package volume (in)	829.32
IP internal	66
Drive Over	No

### Download

[Family spec sheet](#) ZIP

[Mounting instructions](#) ZIP

### Photometric Files

[LDT / IES](#) ZIP




### Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E




Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

## Schematic light drawing



### Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	45
Beam angle C90-270 (°)	20
Extreme cut off	No

### Electrical

Insulation class	III
Driver	Remote
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable DALI PWM, Dimmable 1-10 PWM
Dimming interface	Remote Dimmable (Dimmer Not Included)

### Notes

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges

These effects are frequently caused by:

- over voltage coming from the mains' network where fixture is connected.
- electrostatic discharge (ESD) coming from the environment.

The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.

## Accessories & Power Supply



OPTIONAL  
Accessory

F002Z050070

Anodized aestetcal pole screen  
Anodized Natural



OPTIONAL  
Accessory

F002Z050071

Anodized aestetcal pole screen  
Anodized Black



OPTIONAL  
Accessory

F002Z050073

Anodized aestetcal pole screen  
Anodized Gold



OPTIONAL  
Accessory

F002Z020000

Klein Pro base plate and fixing  
bolts 85x85xH160 mm



OPTIONAL  
Accessory

F002Z010001.A

Fixing base for solid surfaces  
White



OPTIONAL  
Accessory

F002Z030000.A

Minimal Klein Pro ground fixation  
plate, 47x57xH160 mm