

# FLOS

F004B45AU56 Matte Stainless Steel

## Landlord Ground Ø64 4 Beam Non Dimmable Matt Stainless Steel

Designed by Piero Lissoni, 2018



24V remote power supply to be ordered separately. Necessary box for installation, to be ordered separately.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |                      |
|------------------------|----------------------|
| EAN                    | 8054793195704        |
| Mounting               | In-ground            |
| Environments           | Outdoor wet location |
| Light Source Type      | LED                  |
| Light sources included | Yes                  |
| LED type               | Power LED            |
| Number of lamps        | 1                    |
| Power (W)              | 3                    |
| System flux (lm)       | 48                   |

### Physical

|                     |                       |
|---------------------|-----------------------|
| Color               | Matte Stainless Steel |
| Orientation         | Fixed                 |
| Net weight (lb)     | 0.75                  |
| Gross weight (lb)   | 0.84                  |
| Package height (in) | 5.28                  |
| Package width (in)  | 2.76                  |
| Package length (in) | 3.27                  |
| Package volume (in) | 47.54                 |
| IP internal         | 67                    |
| IP external         | 66                    |



### Download

Family spec sheet [ZIP](#)  
Mounting instructions [ZIP](#)

### Photometric Files

LDT / IES [ZIP](#)

### Ecodesign and Energy Labelling


This product contains a light source of energy efficiency class D



Replaceable (LED only)  
light source by a  
professional



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 4000      |
| CRI>                   | 80        |
| Beam angle C0-180 (°)  | 41        |
| Beam angle C90-270 (°) | 41        |

Electrical

|                   |                                       |
|-------------------|---------------------------------------|
| Driver            | Remote excluded                       |
| Dimmable          | Yes                                   |
| Dimming interface | Remote Dimmable (Dimmer Not Included) |

Notes

Carefully install and maintain the fixtures to avoid damaging the coating.  
For LED fixtures, most problems are tied to electrical issues related to the insulation, which may cause destructive electrical discharges.  
These are frequently caused by:

- power surges from the power network where fixture is connected.
- electrostatic discharge (ESD) from the environment.

We recommend installing a power-surge protection device on the fixture to reduce the intensity of these effects and prevent irreversible damages. The specific device should be chosen based on the electrical characteristics.

Accessories & Power Supply



REQUIRED  
Accessory

F004Z0K0000

Box for installation